

JCM INDUSTRIES

P. O. Box 1220, Nash, TX 75569-1220

Phone 800-527-8482 or 903-832-2581

Fax 800-874-9524 or 903-838-6260

www.jcmindustries.com


Typical Specification

JCM 422 Fabricated Tapping Sleeve for PVC and Steel Pipe

Tapping sleeves for 4" through 12" PVC and steel pipe shall be the high strength type having a wide body, made of a minimum material strength of ASTM 285 Grade C Steel, which conforms to and reinforces the pipe. The sleeve shall be sized to fit the exact dimension of the pipe and have 5/8" bolts on 3" centers. The sleeve shall have a Nitrile Butadiene Rubber (NBR, Buna-N) per ASTM D2000 gasket with hydromechanical activated lip, captured in a recessed groove around the outlet. Flanged outlets shall be AWWA C207 Class D, ANSI 150 lb. Drilling, recessed for tapping valve per MSS-SP60. The sleeve shall be fusion epoxy coated to a minimum 12 mils thickness, per ANSI/AWWA C-213 and furnished with a type 304 stainless steel plug in the test outlet. Tapping Sleeves shall be JCM 422 or approved equal.

JCM 400 Series Tapping Sleeves are ANSI/NSF Standard 61 Certified.

JCM 400 Series Tapping Sleeves meet MSS-SP124 and ANSI/AWWA Standard C223 Fabricated Steel and Stainless Steel Tapping Sleeves as applicable.



JCM 422 Tapping Sleeve
Image reflects 8" x 6"

This typical specification, provided by JCM Industries, is a proposed guideline for use by specifying agencies to ensure significant design and material features of this product are included within the agencies' individual specifications.



Effective 04.03.08

JCM INDUSTRIES

P. O. Box 1220, Nash, TX 75569-1220

Phone 800-527-8482 or 903-832-2581

Fax 800-874-9524 or 903-838-6260

www.jcmindustries.com

Material Specifications

JCM 422 Fabricated Tapping Sleeve for PVC and Steel Pipe

Body: ASTM 285 Grade C, ASTM A-36 Steel or equal.

Bolts: 5/8" Corrosion resistant, high strength low alloy oval neck track head bolt per ASTM A242/ANSI 21.11/AWWA C-111 and heavy hex nut per A563 epoxy coated, Powercron 590-534.
Optional: Stainless Steel 18-8 304 or 316 available.

Flange: AWWA C207 Class D, ANSI 150 lb. Drilling, recessed for tapping valve MSS-SP60.

Gasket: Nitrile Butadiene Rubber (NBR, Buna-N) per ASTM D2000. Molded virgin rubber with a pressure activated hydro mechanical design. Gasket is bonded into a cavity for internal and external retention. Gasket temperature range - 40°F to 212°F (-40°C - 100°C) Gasket suitable for water, salt solutions, mild acids, bases, and sewage.

Finish: Fusion applied epoxy coating, minimum 12 mils thickness per ANSI/AWWA C-213.

Service Rating: 4" to 12" Outlets: 175 PSI. Higher service rating available for specific applications and sizes.

JCM 400 Series Tapping Sleeves are ANSI/NSF Standard 61 Certified.

JCM 400 Series Tapping Sleeves meet MSS-SP124 and ANSI/AWWA Standard C223 Fabricated Steel and Stainless Steel Tapping Sleeves as applicable.



JCM INDUSTRIES

P. O. Box 1220, Nash, TX 75569-1220
 Phone 800-527-8482 or 903-832-2581
 Fax 800-874-9524 or 903-838-6260
www.jcmindustries.com

JCM 422 Tapping Sleeve Dimensions

Flange Size	A	B	C	D	E	F
3	9*	5	4-1/32	3-1/2	6	5/8
4	9*	5	5-1/32	4	6	5/8
6	12	5	7-1/32	6-1/8	8	5/8
8	15	5-1/8	9-1/32	8-1/8	10	5/8
10	21	5-1/2	11-1/16	10-1/4	14	5/8
12	24	5-3/4	13-1/16	12-1/4	16	5/8

422 Tapping Sleeves require that a standard 1/2" undersized cutter be used.

*Nominal Pipe Sizes 3", 10" & 12" – dimension A is 12"

