

# JCM 105 Collar Leak Clamps

## JCM 135 All Stainless Steel Collar Leak Clamps

For Quick, Permanent repairs of solvent weld PVC pipe joints.

JCM 105/135 Collar Leak Clamps provide a simple, quick solution to troublesome leaks in PVC solvent weld pipe systems - without having to cut out fittings or modifying your system. These heavy duty clamps have many features which assure a successful repair, even under the most adverse conditions.



### HOW TO ORDER

- |  |  |   |
|--|--|---|
| <p>1. Determine O.D. of pipe.</p> <p>2. Select proper clamp O.D. range and band width.</p> | <p>3. Specify clamp number. For all stainless clamp, change model number to 135.</p> | <p>EXAMPLE:<br/>For 3" Class 160 PVC pipe, order: 105-0350-6.<br/>For All Stainless Clamp, order: 135-0350-6.</p> |
|--|--|---|

NOM. PIPE SIZE (IN.)	PIPE O.D. SIZE (IN.)	TYPE OF SOLVENT WELD PIPE JOINT	Clamp Width*	CLAMP NUMBER	APPR WT. EACH (LBS.)	ALL STAINLESS CLAMP NUMBER	APPR WT. EACH (LBS.)
2	2.38	BELL END CLASS 160, 200 SCH 40 COUPLING AND BELL END	6	105-0238-6	7.3	135-0238-6	5.3
			7	105-0238-7	9.3	135-0238-7	6
2-1/2	2.88	BELL END CLASS 160, 200 SCH 40 COUPLING AND BELL END	6	105-0288-6	7.7	135-0288-6	5.7
			7	105-0288-7	9.9	135-0288-7	6
3	3.50	BELL END CLASS 160, 200 SCH 40 COUPLING AND BELL END	6	105-0350-6	8.0	135-0350-6	6
			7	105-0350-7	10	135-0350-7	7
4	4.50	BELL END CLASS 160, 200 SCH 40 COUPLING AND BELL END	6	105-0450-6	9.1	135-0450-6	6
			7	105-0450-7	11	135-0450-7	7
5	5.56	BELL END CLASS 160, 200 SCH 40 COUPLING AND BELL END	6	105-0556-6	9.4	135-0556-6	6.5
			7	105-0556-7	11	135-0556-7	7
6	6.63	BELL END CLASS 160, 200 SCH 40 COUPLING AND BELLEND	6	105-0663-6	10	135-0663-6	7.5
			7	105-0663-7	12	135-0663-7	8.5
8	8.63	BELL END CLASS 160, 200 SCH 40 COUPLING AND BELL END	6	105-0863-6	11	135-0863-6	8.7
			7	105-0863-7	13	135-0863-7	9.5

\*OTHER WIDTHS AVAILABLE UPON REQUEST

### 105 COLLAR LEAK CLAMP FOR PLASTIC IRRIGATION PIPE

NOM. PIPE SIZE (IN.)	PIPE O.D. SIZE (IN.)	CLAMP WIDTH (IN.)*	FOR PIPE WALL THICKNESS	CLAMP NUMBER	APPR. WT. EA. (LBS.)
4	4.125	6	.125	105-0413-6	9.1
6	6.140	6	.150	105-0614-6	9.8
8	8.160	6	.199	105-0816-6	10.7
10	10.200	6	.249	105-1020-6	14.1
12	12.240	6	.290	105-1224-6	14.9
15	15.300	6	.375	105-1530-6	18.0

\*OTHER WIDTHS AVAILABLE UPON REQUEST