

# JCM 161 Fabricated Lug Stainless Steel Universal Clamps



The JCM 161 Fabricated Lug All Stainless Steel Clamp offers an economical solution to problems such as breaks, splits, cracks, holes in all types of pipe. Available in standard sizes, the 161 is a stainless steel clamp that offers all the benefits of stainless: corrosion resistance, lightweight, flexible yet strong.

Image reflects 7" width

Nom. Pipe Size	Clamp O.D. Range	161 Stainless Steel Universal Clamp Clamp Number	Clamp Width - Approximate Weight					
			7"	12"	15"	18"	24"	30"
			Lbs.#	Lbs.#	Lbs.#	Lbs.#	Lbs.#	Lbs.#
2 - 2-1/2	2.35 - 2.63 2.70 - 3.13	0238	<b>\$111.40</b>	<b>182.70</b>	<b>212.00</b>	-	-	-
		0275	5#	8#	10#			
3	3.46 - 3.70 3.73 - 4.13	0350	<b>133.30</b>	<b>211.40</b>	<b>243.20</b>	-	-	-
		0400	6#	9#	11#			
4	4.45 - 4.75 4.74 - 5.14 4.95 - 5.35 5.22 - 5.62	0450	<b>140.50</b>	<b>217.60</b>	<b>247.10</b>	<b>358.80</b>	<b>440.40</b>	<b>494.00</b>
		0480 0500 0525	7#	10#	12#	17#	20#	24#
6	5.95 - 6.35 6.56 - 6.96 6.85 - 7.25 7.05 - 7.45 7.45 - 7.85	0600	<b>166.30</b>	<b>265.20</b>	<b>295.70</b>	<b>457.80</b>	<b>532.70</b>	<b>590.70</b>
		0663 0690 0710 0745	9#	13#	17#	20#	26#	34#
8	7.95 - 8.35 8.54 - 8.94 8.99 - 9.39 9.27 - 9.67 9.90 - 10.30	0800	<b>192.60</b>	<b>306.70</b>	<b>360.00</b>	<b>513.20</b>	<b>605.70</b>	<b>720.70</b>
		0863 0905 0940 1000	11#	16#	21#	25#	32#	44#
10	10.60 - 11.00 11.04 - 11.44 11.34 - 11.74 11.75 - 12.15 12.00 - 12.40	1075	<b>246.50</b>	<b>385.30</b>	<b>443.80</b>	<b>555.30</b>	<b>790.20</b>	<b>884.40</b>
		1110 1140 1175 1200	15#	18#	24#	30#	36#	50#
12	12.60 - 13.02 13.10 - 13.50 13.40 - 13.80 13.70 - 14.10 14.00 - 14.40	1275	<b>286.80</b>	<b>461.60</b>	<b>549.40</b>	<b>748.80</b>	<b>806.70</b>	<b>1,095.20</b>
		1320 1340 1370 1400	17#	20#	27#	34#	40#	56#
<b>Number of Bolts</b>			<b>2</b>	<b>3</b>	<b>4</b>	<b>4</b>	<b>6</b>	<b>8</b>

## HOW TO ORDER

- Determine O.D. of pipe.
  - Select proper clamp O.D. range and band width.
  - Determine Model Number.
  - Specify clamp number. Example: To fit Cast Iron pipe, 6.90 O.D. with 6" width, order: 161-0690-6
- Clamp width should be equal to or greater than the pipe diameter for higher working pressures. Contact JCM Industries for recommendations.
  - Not recommended for use for joining plain end pressure pipe.
  - Other ranges and widths available upon request.
  - Clamps do not prevent lateral movement of pipe. Applications in which the pipe may move out of the clamp, proper anchorage of the pipe must be provided.



## Available Options Upon Request Models 161-162

- Pipe sizes and ranges not listed
- Conductive Buttons
- Specialty Gaskets
- Tapped clamps, see page 14