

JCM 203 Steel Transition Couplings

The JCM 203 Steel Transition Coupling provides a simple means of joining plain end pipe of the same nominal size but different outside diameter dimensions. The couplings are especially useful in joining old cast iron pipe to ductile iron pipe. Listed are the most common sizes. Other sizes are available upon request. Also see JCM 212 Ductile Iron Couplings.

203 STEEL TRANSITION COUPLINGS

NOM. PIPE SIZE (IN.)	FROM O.D. RANGE (IN.)	TRANSITION TO O.D. RANGE	SLEEVE LENGTH	MIDDLE RING THICKNESS	CATALOG NUMBER	PRICE EACH	APPR. WT. EA. (LBS.)
14	15.65	15.30	7"	3/8"	203-1565-1530	\$ 813.10	85
16	17.80	17.40	7"	3/8"	203-1780-1740	877.10	95
18	19.92	19.50	7"	3/8"	203-1992-1950	985.60	115
20	22.06	21.60	7"	3/8"	203-2206-2160	1,249.20	125
24	26.32	25.80	7"	3/8"	203-2632-2580	1,480.20	145

OTHER SIZES AVAILABLE UPON REQUEST

NOTE: Applications in which pipe may move out of the coupling, correct anchorage of the pipe must be provided.

JCM 204 Steel Reducing Couplings



The JCM 204 Steel Reducing Coupling is the simplest means of connecting any combination of two sizes or types of pipe. There is practically no limit to the pipe sizes that can be connected - either to reduce or increase in size. One common use is joining large steel pipe to ductile iron or C-905 PVC pipe. Listed are the most common sizes. Other sizes are available upon request.

204 STEEL REDUCING COUPLINGS

NOM. PIPE SIZE (IN.)	FROM O.D. RANGE (IN.)	REDUCE TO O.D. RANGE (IN.)	CATALOG NUMBER	PRICE EACH	APPR. WT. EACH (LBS.)
14	15.30	14.00	204-1530-1400	\$ 1,856.40	170
	15.65	14.00	204-1565-1400	1,898.50	170
	16.75	15.30	204-1675-1530	1,937.40	190
16	17.40	16.00	204-1740-1600	1,967.90	195
	17.80	16.00	204-1780-1600	2,012.20	195
	18.88	17.40	204-1888-1740	2,044.00	205
18	19.50	18.00	204-1950-1800	2,110.50	215
	19.92	18.00	204-1992-1800	2,154.50	215
20	21.60	20.00	204-2160-2000	2,300.70	245
	22.06	20.00	204-2206-2000	2,366.00	245
24	25.80	24.00	204-2580-2400	2,527.20	290
	26.32	24.00	204-2632-2400	2,606.20	290

OTHER SIZES AVAILABLE UPON REQUEST

NOTE: Applications in which pipe may move out of the coupling, correct anchorage of the pipe must be provided.

