

JCM 303 Fabricated Flanged Coupling Adapters



The JCM 303 Fabricated Flanged Coupling Adapter provides a simple means of joining plain end pipe to flanged fittings, valves and equipment. Fabricated from steel, these fittings are readily available in large or small sizes with a standard AWWA Class D flange. Special or heavier flanges are available on request.

How To Order

- | | | |
|---|---|---|
| 1. Determine pipe O.D. and flange size & type to be joined. | 2. Order catalog Number indicating O.D. and flange size selected. | EXAMPLE: For 17.40 O.D. ductile iron pipe to be joined to 16" Class D flange, order: 303-1740 x16 |
|---|---|---|

JCM 303 FLANGED COUPLING ADAPTERS

NOM. PIPE SIZE (IN.)	PIPE O.D. RANGE (IN.)	NOMINAL FLANGE SIZE	CATALOG NUMBER	PRICE EACH	APPR. WT. EACH (LBS.)
3	3.50	3	303-0350 X 3	\$ 352.70	19
4	4.50	4	303-0450 X 4	380.30	25
4	4.80 - 5.00	4	303-0480 X 4	430.40	26
5	5.56	5	303-0556 X 5	473.90	32
6	6.63	6	303-0663 X 6	537.80	38
6	6.90 - 7.10	6	303-0690 X 6	555.20	40
8	8.63	8	303-0863 X 8	667.80	50
8	9.05 - 9.30	8	303-0905 X 8	687.80	52
10	10.75	10	303-1075 X 10	837.90	58
10	11.10 - 11.40	10	303-1110 X 10	857.80	61
12	12.75	12	303-1275 X 12	997.00	78
12	13.20 - 13.50	12	303-1320 X 12	1,013.00	84
14	14.00	14	303-1400 X 14	1,153.00	90
14	15.30	14	303-1530 X 14	1,197.90	110
14	15.65	14	303-1565 X 14	1,223.70	110
16	16.00	16	303-1600 X 16	1,290.40	113
16	17.40	16	303-1740 X 16	1,450.40	130
16	17.80	16	303-1780 X 16	1,488.00	137
18	18.00	18	303-1800 X 18	1,532.90	137
18	19.50	18	303-1950 X 18	1,743.10	144
18	19.92	18	303-1992 X 18	1,798.10	144
20	20.00	20	303-2000 X 20	1,835.80	158
20	21.60	20	303-2160 X 20	2,093.20	162
20	22.06	20	303-2206 X 20	2,130.90	162
24	24.00	24	303-2400 X 24	2,256.00	192
24	25.80	24	303-2580 X 24	2,414.30	220
24	26.32	24	303-2632 X 24	2,538.30	220
30	32.00	30	303-3200 X 30	P.O.A.	442
36	38.30	36	303-3830 X 36	P.O.A.	602
42	44.50	42	303-4450 X 42	P.O.A.	771
48	50.80	48	303-5080 X 48	P.O.A.	885

Other sizes available upon request.

Epoxy coating and stainless steel bolts are available as an extra.

NOTE: Applications in which pipe may move out of the coupling, correct anchorage of the pipe must be provided.

