

# JCM Coated Service Saddles - Single Strap

## JCM 405 Single Strap Service Saddle with Stainless Steel Strap

## JCM 407 Wide Body Service Saddle with Electro Galvanized Strap

The **JCM 405 Coated Wide Body Service Saddle with Stainless Steel Strap** is designed for maximum safety and performance in tapping all types of pipe in hot and corrosive soils. Extra corrosion resistance is built into this saddle with the heavy resilient plastic coating which is fusion applied to the saddle body.

The **JCM 407 Coated Wide Body Service Saddle** utilizes an electro galvanized steel strap with the broad, wrap around single strap saddle body. The 407 features the extra corrosion resistance is built into this saddle with the heavy resilient plastic coating which is fusion applied to the saddle body.


NOM. PIPE SIZE (IN.)	PIPE O.D. RANGE (IN.)	APPR WT. EACH (LBS.)	CTN. QTY.	JCM 405 SERVICE SADDLE			JCM 407 SERVICES SADDLE		
				CATALOG NUMBER X TAP CODE	3/4" & 1" PRICE EACH	1-1/4", 1-1/2", 2", 2-1/2" PRICE EACH	CATALOG NUMBER X TAP CODE	3/4" & 1" PRICE EACH	1-1/4", 1-1/2", 2", 2-1/2" PRICE EACH
2	2.35 - 2.63	2.5	12	405-0238 X --	\$ 56.20	N/A	407-0238 X --	\$ 34.00	N/A
2-1/2	2.70 - 3.13	3.0	12	405-0288 X --	57.20	N/A	407-0288 X --	35.40	N/A
3	3.25 - 3.50	3.0	12	405-0350 X --	57.20	N/A	407-0350 X --	37.30	N/A
3 - 4	3.80 - 4.13	3.0	12	405-0413 X --	58.40	N/A	N/A	N/A	N/A
4	4.25 - 4.50	4.5	10	405-0450 X --	58.40	\$ 70.80	407-0450 X --	39.60	\$ 53.80
4	4.50 - 4.80	4.5	10	405-0480 X --	58.70	70.80	407-0480 X --	42.10	53.80
4	4.74 - 5.45	4.5	10	405-0545 X --	58.70	N/A	407-0545 X --	42.10	N/A
6	6.50 - 6.63	4.5	10	405-0663 X --	65.90	79.10	407-0663 X --	44.40	60.80
6	6.63 - 6.90	4.5	10	405-0690 X --	66.70	80.20	407-0690 X --	47.00	64.60
6	6.84 - 7.60	4.5	10	405-0745 X --	66.70	80.20	407-0745 X --	47.00	64.60
8	8.50 - 8.63	5.0	10	405-0863 X --	77.60	92.40	407-0863 X --	53.40	70.60
8	8.63 - 9.05	5.0	10	405-0905 X --	79.40	93.90	407-0905 X --	55.80	81.30
8	8.99 - 9.79	5.0	10	405-0963 X --	79.40	93.90	407-0963 X --	55.80	81.30
10	10.60 - 10.75	5.5	6	405-1075 X --	87.30	110.10	407-1075 X --	67.30	97.90
10	10.75 - 11.10	5.5	6	405-1110 X --	87.30	110.10	407-1110 X --	67.30	97.90
10	11.10 - 11.40	5.5	6	405-1140 X --	87.30	110.10	407-1140 X --	67.30	97.90
10	11.00 - 12.25	5.5	6	405-1225 X --	87.30	110.10	407-1225 X --	67.30	97.90
12	12.60 - 12.75	6.0	6	405-1275 X --	100.60	128.50	407-1275 X --	71.90	100.00
12	12.75 - 13.20	6.0	6	405-1320 X --	100.60	128.50	407-1320 X --	71.90	100.00
12	12.75 - 13.50	6.0	6	405-1350 X --	100.60	128.50	407-1350 X --	71.90	100.00
12	13.10 - 14.38	6.0	4	405-1426 X --	100.60	128.50	407-1426 X --	71.90	100.00

### How To Order

1. Determine O.D. of pipe, outlet size and thread type.
2. Select desired saddle type and tap order code.
3. Look under saddle listing to determine order number. Add tap code after base catalog number.

**EXAMPLE:** For 6" C.I. Pipe with O.D. of 6.90 with 1" IP thread, order: 405-0745 x 08IP. For electro galvanized strap, order: 407-0745 x 08IP.

OUTLET SIZES	TAP CODES IP	TAP CODES CC
1/2"	04	--
3/4"	06	07
1"	08	09
1-1/4"	10	11
1-1/2"	12	13
2"	14	15
2-1/2"	16	--



**JCM 403/405 Strap Service Saddles with outlets 1-1/4" - 2-1/2"**

